
Configuration snippets

Various forms configurations

1. Simple form with 3 fields: text, textarea and user field



Configuration in the editor



Storage format for you to import


```
<ac:structured-macro ac:macro-id="27a53aa2-bc57-43c5-b6df-566cbada8e7a" ac:name="confiform" ac:schema-
version="1">
  <ac:parameter ac:name="formName">simpleForm</ac:parameter>
  <ac:rich-text-body>
    <p>
      <ac:structured-macro ac:name="confiform-field-definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">mytextfield</ac:parameter>
        <ac:parameter ac:name="fieldLabel">My Text Field</ac:parameter>
        <ac:parameter ac:name="type">text</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:name="confiform-field-definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">textAreaField</ac:parameter>
        <ac:parameter ac:name="fieldLabel">My textarea field</ac:parameter>
        <ac:parameter ac:name="type">textarea</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:name="confiform-field-definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">theUser</ac:parameter>
        <ac:parameter ac:name="fieldLabel">User</ac:parameter>
        <ac:parameter ac:name="type">user</ac:parameter>
      </ac:structured-macro>
      <ac:structured-macro ac:name="confiform-entry-register" ac:schema-version="1">
        <ac:parameter ac:name="atlassian-macro-output-type">INLINE</ac:parameter>
        <ac:rich-text-body>
          <p> </p>
        </ac:rich-text-body>
      </ac:structured-macro>
    </p>
  </ac:rich-text-body>
</ac:structured-macro>
```

2. Using ConfiForms TableView macro to show the content of previous form

   On the page

User	My Text Field	My textarea field
Sash [ConfiForms]	Test	Some text in text area field


   In the editor

   Storage format

```
<ac:structured-macro ac:name="confiform-table" ac:schema-version="1">
  <ac:parameter ac:name="formName">simpleForm</ac:parameter>
  <ac:rich-text-body>
    <p>
      <ac:structured-macro ac:name="confiform-field" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">theUser</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:name="confiform-field" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">mytextfield</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:name="confiform-field" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">textAreaField</ac:parameter>
      </ac:structured-macro>
    </p>
  </ac:rich-text-body>
</ac:structured-macro>
```

3. Showing the same form using ConfiForms ListView
   On the page



In the editor



Storage format

```
<ac:structured-macro ac:name="confiform-list" ac:schema-version="1">
  <ac:parameter ac:name="formName">simpleForm</ac:parameter>
  <ac:rich-text-body>
    <h2> <ac:structured-macro ac:name="confiform-field" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">theUser</ac:parameter>
      </ac:structured-macro>
    </h2>
    <table>
      <tbody>
        <tr>
          <td>
            <p>Value for text field (just adding some text before the value):</p>
            <p>
              <ac:structured-macro ac:name="confiform-field" ac:schema-version="1">
                <ac:parameter ac:name="fieldName">mytextfield</ac:parameter>
              </ac:structured-macro>
            </p>
            <p> </p>
          </td>
          <td>
            <p>
              <ac:structured-macro ac:name="confiform-field" ac:schema-version="1">
                <ac:parameter ac:name="fieldName">textAreaField</ac:parameter>
              </ac:structured-macro>
            </p>
            <p> </p>
          </td>
        </tr>
      </tbody>
    </table>
  </ac:rich-text-body>
</ac:structured-macro>
```



Take a look at Tutorials to get examples of more complex configurations, as ConfiForms is very versatile in functionality and supports many use-cases and scenarios