

Create Jira issue with webservice connection with files and remote links

Yes, you can create Jira issue with WebService IFTTT action (usual IFTTT to create Jira issues will not work for anonymous users as it does uses the Application link to connect to your Jira and that will not be available for anonymous users, while web service connection is available to anyone, unless you tell otherwise (setting up connection restrictions))

Here is the demo (creates the issue and stores the Jira key back)

Visual view in the editor

The screenshot displays the ConfForms editor interface. At the top, a header bar shows 'ConfForms Form Definition | formName = ji | registrationFormTitle = Create JIRA issue with ConfForms Webservice co...'. Below this, a section titled 'ConfForms (FormView) Registrations Control | registrationButtonLabel = Register me | overrideSaveButtonLabel = Create | embedded = t...' is visible. The main area contains several 'ConfForms Form Field Definition' blocks for fields like 'summary', 'desc1', 'desc2', 'jk', and 'fi'. A 'ConfForms Rules for Field Definition' block is also present. At the bottom, a 'ConfForms IFTTT Integration Rules' block is shown with the following configuration: event = onCreated, action = WebService Request, title = /rest/api/2/issue/, and who = PO... The IFTTT rule's payload is displayed in a 'No Format' view, showing a JSON object with fields for project (JTEST), summary, assignee (admin), description (concatenated from desc1 and desc2), and issuetype (Bug).

```
{
  "fields": {
    "project": {
      "key": "JTEST"
    },
    "summary": "[entry.summary.escapeJSON]",
    "assignee": {"name": "admin"},
    "description": "[entry.desc1.escapeJSON] \n [entry.desc2.escapeJSON]",
    "issuetype": {
      "name": "Bug"
    }
  }
}
```

ConfifForms IFTTT Integration Rules | event = onCreated | action = Create ConfifForms Entry | title = entryId=[entry.id]&jk=[i...

ConfifForms IFTTT Integration Rules | event = onCreated | action = Webservice Request | title = /rest/api/latest/issue/entry...

ConfifForms Form Field | fieldName = fi

ConfifForms IFTTT Integration Rules | event = onCreated | action = Webservice Request | title = /rest/api/latest/issue/entry...

No Format

```
{  "object": {    "url": "https://wiki.vertuna.com/pages/viewpage.action?pageId=19104427",    "title": "[entry._page.title.escapeJSON]"  }}
```

Source code for the solution

[Create Jira issue with webservice connection with files and remote links - storage format](#)

note that you need to configure webservice connection to something like this

WS Connection Configuration

Name: *

The name for your configuration, will be visible to users

WS URL

Enter with protocol (http:// or https://). This URL will be combined together with the service URL you setup. For WS-backed fields in ConfifForms you service must accept GET requests and return JSON as a result

Username

Leave empty, if the connection requires **no authentication**

Password

Restrictions

Comma separated user groups and/or users who should have access to this configuration. Blank, means no restrictions - everyone can use it

Save

Close

The table is created like this

```
<ac:structured-macro ac:macro-id="d309c641-56ef-46cb-b01f-19590d41605e" ac:name="conform-table" ac:schema-version="1">
  <ac:parameter ac:name="formName">ji</ac:parameter>
  <ac:rich-text-body>
    <p>
      <ac:structured-macro ac:macro-id="bb4766d6-cbfe-40c6-ace4-f3dcd21dcc99" ac:name="conform-field" ac:
schema-version="1">
        <ac:parameter ac:name="fieldName">jk.asJSON.key</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="18b7e9fe-30c3-4a04-886e-6a47446af441" ac:name="conform-field" ac:
schema-version="1">
        <ac:parameter ac:name="fieldName">created</ac:parameter>
      </ac:structured-macro>
    </p>
  </ac:rich-text-body>
</ac:structured-macro>
```

Using asJSON function as a bridge ([Virtual functions](#)) and accessing the issue key (key property)

```
jk.asJSON.key
```

- [Create Jira issue with webservice connection with files and remote links - storage format](#)