

Smart dropdown with a text field to add new custom choice

Page contains 2 forms

- to store the choices
- to allow users to select a choice or add new one via text field

Uses ConfiForms IFTTT to add an option into the "choices" form

Register

Register

```

<ac:structured-macro ac:macro-id="df4a616e-0206-4017-a7ea-96fe85f19f64" ac:name="conform" ac:schema-version="1">
  <ac:parameter ac:name="formName">choices1</ac:parameter>
  <ac:rich-text-body>
    <p>
      <ac:structured-macro ac:macro-id="ac87a109-eb3c-4b09-bf42-4502bb39c32f" ac:name="conform-field-definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">choice</ac:parameter>
        <ac:parameter ac:name="fieldLabel">Choice</ac:parameter>
        <ac:parameter ac:name="type">text</ac:parameter>
      </ac:structured-macro>
    </p>
    <ac:structured-macro ac:macro-id="6a3db5cc-f2d4-4425-852c-667e2ab73446" ac:name="conform-entry-register" ac:schema-version="1">
      <ac:rich-text-body>
        <p> </p>
      </ac:rich-text-body>
    </ac:structured-macro>
  </ac:rich-text-body>
</ac:structured-macro>
<ac:structured-macro ac:macro-id="741bee2a-a8e6-4100-899b-c827ab4ee90a" ac:name="conform" ac:schema-version="1">
  <ac:parameter ac:name="formName">mychoices1</ac:parameter>
  <ac:rich-text-body>
    <p>
      <ac:structured-macro ac:macro-id="45a80c97-4b78-45cf-9f2c-2e6c0a965599" ac:name="conform-field-definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">makeChoice</ac:parameter>
        <ac:parameter ac:name="fieldLabel">Make a choice</ac:parameter>
        <ac:parameter ac:name="values">[9371754|choices|choice|true||]</ac:parameter>
        <ac:parameter ac:name="type">smartselect</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="b5c7b3d1-d089-4967-848c-009ab846b2dc" ac:name="conform-field-definition-rules" ac:schema-version="1">
        <ac:parameter ac:name="condition">makeChoice.choice:Other</ac:parameter>
        <ac:parameter ac:name="fieldName">ownChoice</ac:parameter>
        <ac:parameter ac:name="action">Show field</ac:parameter>
        <ac:parameter ac:name="actionFieldName">makeChoice</ac:parameter>
        <ac:parameter ac:name="withReverseRule">true</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="e46a185f-b4c2-4e9b-b2b8-f7f318f011a9" ac:name="conform-field-definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">ownChoice</ac:parameter>
        <ac:parameter ac:name="fieldLabel">Other</ac:parameter>
        <ac:parameter ac:name="type">text</ac:parameter>
      </ac:structured-macro>
    </p>
    <ac:structured-macro ac:macro-id="48d7cf7f-43d0-4314-abc0-22595f53f328" ac:name="conform-entry-register" ac:schema-version="1">
      <ac:rich-text-body>
        <p> </p>
      </ac:rich-text-body>
    </ac:structured-macro>
    <ac:structured-macro ac:macro-id="7e6740f7-1597-4e73-960d-86812145cf2e" ac:name="conform-ifttt" ac:schema-version="1">
      <ac:parameter ac:name="action">Create ConfiForms Entry</ac:parameter>
      <ac:parameter ac:name="event">onCreated</ac:parameter>
      <ac:parameter ac:name="title">choice=[entry.ownChoice]</ac:parameter>
      <ac:parameter ac:name="who">choices1:9371754</ac:parameter>
      <ac:parameter ac:name="condition">!ownChoice:[empty]</ac:parameter>
      <ac:rich-text-body>
        <p> </p>
      </ac:rich-text-body>
    </ac:structured-macro>
  </ac:rich-text-body>
</ac:structured-macro>

```



Make sure to change the page id in the destination for IFTTT macro (where the record will be added)

```
<ac:parameter ac:name="who">choices1:9371754</ac:parameter>
```