Create Jira issue, save the created Jira key back to ConfiForms and create a page with Jira macro

In this tutorial you will learn how to create Jira issue with Jira key saved back to ConfiForms form and create a page with Jira macro.

Video

Your browser does not support the HTML5 video element

Source code for the solution

```
<ac:structured-macro ac:macro-id="e4269d64-4a3b-4d4c-81fd-7878c4087f34" ac:name="confiform" ac:schema-version="
1">
  <ac:parameter ac:name="formName">f</ac:parameter>
  <ac:rich-text-body>
    <ac:structured-macro ac:macro-id="d2653524-c307-4e83-bfa9-83eb42abb794" ac:name="confiform-entry-register"
ac:schema-version="1">
      <ac:parameter ac:name="embedded">true</ac:parameter>
      <ac:rich-text-body>
        <p> </p>
      </ac:rich-text-body>
    </ac:structured-macro>
    <p>
      <ac:structured-macro ac:macro-id="8c8c2476-c782-42d6-9e5c-91a12d327879" ac:name="confiform-field-
definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">JIRAKey</ac:parameter>
        <ac:parameter ac:name="fieldLabel">JIRAKey</ac:parameter>
        <ac:parameter ac:name="type">text</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="5937f524-4a67-446d-b38f-aaaff744fbba" ac:name="confiform-field-
definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">pageTitle</ac:parameter>
        <ac:parameter ac:name="fieldLabel">Page title</ac:parameter>
        <ac:parameter ac:name="type">text</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="38ffeb83-fe68-4e4b-847b-15976468b5ed" ac:name="confiform-field-
definition-rules" ac:schema-version="1">
        <ac:parameter ac:name="condition">id:[empty]</ac:parameter>
        <ac:parameter ac:name="fieldName">JIRAKey</ac:parameter>
        <ac:parameter ac:name="action">Hide field</ac:parameter>
      </ac:structured-macro>
    </p>
    <p> </p>
    <p>--- creates issue</p>
    <ac:structured-macro ac:macro-id="4599f927-d2c0-4a3b-a20b-de65b9374e75" ac:name="confiform-ifttt" ac:schema-
version="1">
      <ac:parameter ac:name="action">Create JIRA Issue</ac:parameter>
      <ac:parameter ac:name="event">onCreated</ac:parameter>
      <ac:parameter ac:name="resultName">myjiracreator</ac:parameter>
      <ac:rich-text-body>
        <ac:structured-macro ac:macro-id="ccb6d35a-0ea8-4792-b569-e6176ca2dbad" ac:name="noformat" ac:schema-
version="1">
          <ac:plain-text-body><![CDATA[{
    "fields": {
       "project":
       {
          "key": "JTEST"
       },
       "summary": "TEST Issue - [entry.pageTitle]",
       "issuetype": {
          "name": "Bug"
       }
   }
```

```
}]]></ac:plain-text-body>
        </ac:structured-macro>
      </ac:rich-text-body>
    </ac:structured-macro>
    <p>-- updates jirakey back to confiforms record</p>
    <ac:structured-macro ac:macro-id="8eb89451-5f83-40ed-8c5f-616384c558ba" ac:name="confiform-ifttt" ac:schema-
version="1">
      <ac:parameter ac:name="action">Create ConfiForms Entry</ac:parameter>
      <ac:parameter ac:name="event">onCreated</ac:parameter>
      <ac:parameter ac:name="title">entryId=[entry.id]&amp;amp;JIRAKey=${iftttResult_myjiracreator}</ac:parameter>
      <ac:rich-text-body>
        <p> </p>
      </ac:rich-text-body>
    </ac:structured-macro>
    <p>creates a page</p>
    <ac:structured-macro ac:macro-id="fee11aaf-7a66-47f6-80cd-a7aef225037d" ac:name="confiform-ifttt" ac:schema-
version="1">
      <ac:parameter ac:name="action">Create Page</ac:parameter>
      <ac:parameter ac:name="event">onCreated</ac:parameter>
      <ac:parameter ac:name="title">[entry.pageTitle]</ac:parameter>
      <ac:rich-text-body>
        <p>Confluence JIRA macro to show JIRA issue created</p>
        <p>
          <ac:structured-macro ac:macro-id="af9653df-d390-41b3-834a-886902200d5c" ac:name="jira" ac:schema-
version="1">
            <ac:parameter ac:name="server">JIRA</ac:parameter>
            <ac:parameter ac:name="columns">key,summary,type,created,updated,due,assignee,reporter,priority,
status,resolution</ac:parameter>
            <ac:parameter ac:name="maximumIssues">20</ac:parameter>
            <ac:parameter ac:name="jqlQuery">key = [entry.JIRAKey] OR parent = [entry.JIRAKey]</ac:parameter>
            <ac:parameter ac:name="serverId">e448067e-a16a-3ba7-893b-87a33aec6e05</ac:parameter>
          </ac:structured-macro>
        </p>
      </ac:rich-text-body>
    </ac:structured-macro>
  </ac:rich-text-body>
</ac:structured-macro>
<p> </p>
<p>All records in my form</p>
<ac:structured-macro ac:macro-id="9f3b1337-876d-42f0-abef-11bdc68ea23c" ac:name="confiform-table" ac:schema-
version="1">
  <ac:parameter ac:name="messageToShowWhenEmpty">No records yet</ac:parameter>
  <ac:parameter ac:name="formName">f</ac:parameter>
  <ac:rich-text-body>
    <p>
      <ac:structured-macro ac:macro-id="24b6c232-b24d-4e41-88b8-a2f261b261ee" ac:name="confiform-field" ac:
schema-version="1">
        <ac:parameter ac:name="fieldName">JIRAKey</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="63fcb683-1b1c-4468-a813-5bec550fc51c" ac:name="confiform-field" ac:
schema-version="1">
        <ac:parameter ac:name="fieldName">pageTitle</ac:parameter>
      </ac:structured-macro>
    </p>
  </ac:rich-text-body>
</ac:structured-macro>
<p> </p>
<p>Created pages:</p>
<p>
  <ac:structured-macro ac:macro-id="3c94ade2-8334-4c86-ab5a-7cca49d3b018" ac:name="children" ac:schema-version="
2"/>
</p>
```