

a form with duplicated created and createdby in readonly fields

In this demo we copy the created and createdBy into other readonly fields we have on our form

- 2 Readonly fields to hold the values from metadata fields, fields are hidden when a user creates an entry with ConfiForms Field Definition Rule
- ConfiForms IFTTT macro is used on "created" event to copy the values from metadata fields "created" and createdBy into our read-only fields

Register

[View in the editor](#)

The screenshot displays the ConfiForms editor interface for a form named "myform". The interface is organized into several sections, each with a "CONF" icon and a title. The sections are as follows:

- ConfiForms Form (Definition) | formName = myform**: The top-level configuration section.
- ConfiForms (Form View) Registrations Control**: A section for managing form registrations, currently empty.
- ConfiForms Form Field (Definition) | fieldName = sometext | fiel...**: A configuration for a text field.
- ConfiForms Form Field (Definition) | fieldName = created1 | fiel...**: A configuration for a field named "created1".
- ConfiForms Form Field (Definition) | fieldName = createdBy1 | fi...**: A configuration for a field named "createdBy1".
- ConfiForms Rules for Field Definition | condition = id:[empty] | ac...**: A configuration for a field definition rule.
- ConfiForms IFTTT Integration Rules | event = onCreated | action = Create ConfiForms Entry | title = entryId=[entry.id]&creat...**: A configuration for an IFTTT integration rule that triggers on the "onCreated" event and performs the action "Create ConfiForms Entry".

[Source code for the scenario](#)

```

<ac:structured-macro ac:macro-id="b4698dcf-e1f3-414c-8fcc-d11618aaefd7" ac:name="confiiform" ac:schema-version="1">
  <ac:parameter ac:name="formName">myform1</ac:parameter>
  <ac:rich-text-body>
    <ac:structured-macro ac:macro-id="bb9b7b30-d316-4abc-8df5-80e324ee2684" ac:name="confiiform-entry-register"
ac:schema-version="1">
      <ac:parameter ac:name="atlassian-macro-output-type">INLINE</ac:parameter>
      <ac:rich-text-body>
        <p>
          <br/>
        </p>
      </ac:rich-text-body>
    </ac:structured-macro>
  <p>
    <ac:structured-macro ac:macro-id="009183a2-a1c7-4198-a8be-5b22b3b0b983" ac:name="confiiform-field-
definition" ac:schema-version="1">
      <ac:parameter ac:name="fieldName">sometext</ac:parameter>
      <ac:parameter ac:name="fieldLabel">Put some text into this field</ac:parameter>
      <ac:parameter ac:name="fieldDescription">just some text, not important</ac:parameter>
      <ac:parameter ac:name="type">text</ac:parameter>
    </ac:structured-macro>
  </p>
  <p>
    <ac:structured-macro ac:macro-id="3a92e7fa-fb74-4b3b-a8be-ec859947cb94" ac:name="confiiform-field-
definition" ac:schema-version="1">
      <ac:parameter ac:name="fieldName">created1</ac:parameter>
      <ac:parameter ac:name="fieldLabel">Created copy</ac:parameter>
      <ac:parameter ac:name="type">read_only</ac:parameter>
    </ac:structured-macro>
  </p>
  <p>
    <ac:structured-macro ac:macro-id="76727d58-26a1-42ec-a497-125044b4b8d8" ac:name="confiiform-field-
definition" ac:schema-version="1">
      <ac:parameter ac:name="fieldName">createdBy1</ac:parameter>
      <ac:parameter ac:name="fieldLabel">CreatedBy copy</ac:parameter>
      <ac:parameter ac:name="type">read_only</ac:parameter>
    </ac:structured-macro>
  </p>
  <p>
    <ac:structured-macro ac:macro-id="d5f01f52-422d-4bab-9c62-4fc112709214" ac:name="confiiform-field-
definition-rules" ac:schema-version="1">
      <ac:parameter ac:name="condition">id:[empty]</ac:parameter>
      <ac:parameter ac:name="fieldName">created1,createdBy1</ac:parameter>
      <ac:parameter ac:name="action">Hide field</ac:parameter>
    </ac:structured-macro>
  </p>
  <ac:structured-macro ac:macro-id="de6bc21f-983b-4882-b99f-297258d4e235" ac:name="confiiform-ifttt" ac:schema-
version="1">
    <ac:parameter ac:name="extras3">true</ac:parameter>
    <ac:parameter ac:name="extras4">true</ac:parameter>
    <ac:parameter ac:name="action">Create ConfiForms Entry</ac:parameter>
    <ac:parameter ac:name="event">onCreated</ac:parameter>
    <ac:parameter ac:name="title"> entryId=[entry.id]&amp;created1=[entry.created.formatDate(dd.MM.yyyy)]&amp;
createdBy1=[entry.createdBy.fullName]</ac:parameter>
    <ac:rich-text-body>
      <p>
        <br/>
      </p>
    </ac:rich-text-body>
  </ac:structured-macro>
</ac:rich-text-body>
</ac:structured-macro>

```