Using smart fields to pre-set the data

SuppliesTable

ID	Item Code	Item Name	Item Cost
1	C100	Chair	100
2	C200	Desk	300

Using SuppliesTable

Item name and item cost are shown in readonly fields and are copied from item field, from supplies table

Item C100C200

Item Name

Item Cost

Save

Storage format

```
<ac:structured-macro ac:macro-id="cd46e447-5b84-43db-bf7e-0bdec52c79e1" ac:name="confiform" ac:schema-version="
1">
  <ac:parameter ac:name="formName">SuppliesTable1</ac:parameter>
  <ac:rich-text-body>
    <ac:structured-macro ac:macro-id="bdb381b4-f26f-4856-b360-8fbb2ee4da5a" ac:name="confiform-entry-register"
ac:schema-version="1">
      <ac:parameter ac:name="atlassian-macro-output-type">INLINE</ac:parameter>
      <ac:rich-text-body>
        <p>
          <br/>
        </p>
      </ac:rich-text-body>
    </ac:structured-macro>
    <p>
      <ac:structured-macro ac:macro-id="130e60ed-d8d2-46f9-bb38-10a8abf04ea6" ac:name="confiform-field-
definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">itemId</ac:parameter>
        <ac:parameter ac:name="fieldLabel">ID</ac:parameter>
        <ac:parameter ac:name="type">auto</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="3b967ce9-3dee-4fc3-b692-9c3345e24614" ac:name="confiform-field-
definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">itemCode</ac:parameter>
        <ac:parameter ac:name="fieldLabel">Item Code</ac:parameter>
        <ac:parameter ac:name="type">text</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="d2c4a582-c295-43f5-aaa5-f1fb217a33bb" ac:name="confiform-field-
```

```
definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">itemName</ac:parameter>
        <ac:parameter ac:name="fieldLabel">Item Name</ac:parameter>
        <ac:parameter ac:name="type">text</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="cb44c0ea-992b-4300-929f-de1b6ac2a8cf" ac:name="confiform-field-
definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">itemCost</ac:parameter>
        <ac:parameter ac:name="fieldLabel">Item Cost</ac:parameter>
        <ac:parameter ac:name="type">number</ac:parameter>
      </ac:structured-macro>
    </p>
  </ac:rich-text-body>
</ac:structured-macro>
<h2>SuppliesTable</h2>
<ac:structured-macro ac:macro-id="cdc38bfe-68a7-4c4b-bd03-b57c9d542269" ac:name="confiform-table" ac:schema-
version="1">
  <ac:parameter ac:name="formName">SuppliesTable1</ac:parameter>
  <ac:rich-text-body>
    <p>
      <ac:structured-macro ac:macro-id="e128ea0d-3cc4-43f9-a830-79f8cda72402" ac:name="confiform-field" ac:
schema-version="1">
        <ac:parameter ac:name="fieldName">itemId</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="9710f4c5-e2fc-4136-a206-09a4ace1e29f" ac:name="confiform-field" ac:
schema-version="1">
        <ac:parameter ac:name="fieldName">itemCode</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="95444129-3869-470f-9922-e35222d460ae" ac:name="confiform-field" ac:
schema-version="1">
        <ac:parameter ac:name="fieldName">itemName</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="4e866102-dded-4eec-b176-c669a25cbb44" ac:name="confiform-field" ac:
schema-version="1">
        <ac:parameter ac:name="fieldName">itemCost</ac:parameter>
      </ac:structured-macro>
    </p>
  </ac:rich-text-body>
</ac:structured-macro>
<h2>Using SuppliesTable</h2>
<p>Item name and item cost are shown in readonly fields and are copied from item field, from supplies table</p>
<ac:structured-macro ac:macro-id="82ba631a-6b20-42ea-b579-f9825c2fb0d3" ac:name="confiform" ac:schema-version="
1">
  <ac:parameter ac:name="formName">usingSuppliesTable1</ac:parameter>
  <ac:rich-text-body>
    <ac:structured-macro ac:macro-id="7f4f8b27-a14a-4307-84c5-982516207eb2" ac:name="confiform-entry-register"
ac:schema-version="1">
      <ac:parameter ac:name="formName">usingSuppliesTable1</ac:parameter>
      <ac:parameter ac:name="embedded">true</ac:parameter>
      <ac:parameter ac:name="atlassian-macro-output-type">INLINE</ac:parameter>
      <ac:rich-text-body>
        <p>
          <br/>
        </p>
      </ac:rich-text-body>
    </ac:structured-macro>
    <p>
      <ac:structured-macro ac:macro-id="f9c306f5-185e-4d90-b2e4-130735161601" ac:name="confiform-field-
definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">item</ac:parameter>
        <ac:parameter ac:name="fieldLabel">Item</ac:parameter>
        <ac:parameter ac:name="values">[27230635|SuppliesTable1|itemCode|true||]</ac:parameter>
        <ac:parameter ac:name="type">smartselect</ac:parameter>
```

```
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="2f8374bc-42fb-4a1f-afb8-4e5da414dd91" ac:name="confiform-field-
definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">itemName</ac:parameter>
        <ac:parameter ac:name="fieldLabel">Item Name</ac:parameter>
        <ac:parameter ac:name="type">text</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="e6fd3e2e-9fae-4446-b707-1d229d191cff" ac:name="confiform-field-
definition" ac:schema-version="1">
        <ac:parameter ac:name="fieldName">itemCost</ac:parameter>
        <ac:parameter ac:name="fieldLabel">Item Cost</ac:parameter>
        <ac:parameter ac:name="type">number</ac:parameter>
      </ac:structured-macro>
    </p>
    <p>
      <ac:structured-macro ac:macro-id="a6411f3f-bd3a-4a38-acf4-305a26a6ae42" ac:name="confiform-field-
definition-rules" ac:schema-version="1">
        <ac:parameter ac:name="condition">!item:[empty]</ac:parameter>
        <ac:parameter ac:name="values">itemName=[entry.item.itemName]&amp;amp;itemCost=[entry.item.itemCost]</ac:
parameter>
        <ac:parameter ac:name="action">Set value</ac:parameter>
        <ac:parameter ac:name="actionFieldName">item</ac:parameter>
      </ac:structured-macro>
    </p>
  </ac:rich-text-body>
</ac:structured-macro>
```