

# Multi-page view

This macro emulates a multi-page view for the contents. Very useful when used in Combination with ConfiForms custom layout

Here is online demo

This is my page 1

Hello info

It uses [Div container](#) user macro

Here is how it is configured. We have 3 divs, with IDs given as mypage1, mypage2 and mypage3. Also for mypage2 and mypage3 we setup CSS to make them hidden on load

HTML DIV Container | Id = mypage1

This is my page 1

Info

Hello info

HTML DIV Container | Id = mypage2 | Css = display:none;

This is my page 2

Warning

Hello warning

HTML DIV Container | Id = mypage3 | Css = display:none;

This is my page 3

I AM FINE - T...

Shows elements in a multi page view | Pages = mypage1,mypage2,myp...

And we have setup the macro to work on these DIV elements, giving as parameter their IDs in a comma separated format

## Source code for user macro

### Macro Browser Information

Macro Name \*  Macro names are converted to lower case

Visibility  Visible to all users in the Macro Browser  Visible only to system administrators in the Macro Browser

Macro Title \*

Description

Categories  Administration  Communication  Confluence content  Development  External content

Icon URL  Absolute URL (e.g. <http://mysite.com/myimage.png>), or relative to the Confluence base URL (e.g. [/images/logo/confluence\\_48\\_white.png](#))

Documentation URL

### Definition of User Macro

Macro Body  No macro body  Escaped  Unrendered  Rendered

Processing You should use this option for bodies that are processed within the template before being output. Ensure that HTML is ultimately output by the template.

The body will be rendered so most HTML entered will be passed to the template unmodified but Confluence specific mark up such as macro definitions will be rendered.

Template \* 

```
<script type="text/javascript">
AJS.toInit(function() {
#ifeval{$paramManualInit}
#else
initCfDialogPages();
#end
});

function initCfDialogPages() {
var pagesParam = '${paramPages}';
var pages = pagesParam.split(',');
for(i=0;i<pages.length;i++) {
AJS.$("div[id='"+pages[i]+"']").each(function(){
```

## Full source code used in user macro template

```

## @param Pages:title=Comma separated list of element IDs|type=string|required=true|desc=
## @param manualInit:title=Manual initialisation|type=boolean|required=false|desc=Initialises pages on load.
Uncheck this option to auto-initialise, Check this option if you plan to initialise manually, by calling
initCfDialogPages() method

<script type="text/javascript">

AJS.toInit(function() {
    #if(${paramManualInit})
    #else
        initCfDialogPages();
    #end
});;

function initCfDialogPages() {
    var pagesParam = '${paramPages}';
    var pages = pagesParam.split(',');

    for(i=0;i<pages.length;i++) {
        AJS.$("div[id='"+pages[i]+"']").each(function(){
            AJS.$(this).find('.cf-dialog-nav-btns').remove();
        });
        if (i > 0) {
            AJS.$("div[id='"+pages[i]+"']").each(function(){
                AJS.$(this).append('<button type="button" class="aui-button cf-dialog-nav-btns" data-current="'+pages[i]+'" data-div="'+pages[i-1]+'" onclick="showPageDiv(this)">Previous</button>');
            });
        }
        if (i < pages.length-1) {
            AJS.$("div[id='"+pages[i]+"']").each(function(){
                AJS.$(this).append('<button type="button" class="aui-button cf-dialog-nav-btns" data-current="'+pages[i]+'" data-div="'+pages[i+1]+'" onclick="showPageDiv(this)">Next</button>');
            });
        }
    }
}

function showPageDiv(btn) {
    var currentDiv = AJS.$(btn).attr('data-current');
    var showDiv = AJS.$(btn).attr('data-div');

    AJS.$("div[id='"+currentDiv+"']").each(function(){
        AJS.$(this).hide();
    });
    AJS.$("div[id='"+showDiv+"']").each(function(){
        AJS.$(this).show();
    });
}

</script>

```

Here is how it can be used with ConfiForms - simple form with just one field and the same dialog "pages"

As you can see, we use the setting to initialize this widget manually, and have a Field Definition rule that calls "initCfDialogPages" method on form load

```

<ac:structured-macro ac:macro-id="c765a46a-8d0c-479c-9775-7f64e3d5cb97" ac:name="confiform" ac:schema-version="1">
    <ac:parameter ac:name="formName">myform</ac:parameter>
    <ac:rich-text-body>
        <p>
            <br/>
        </p>
        <ac:structured-macro ac:macro-id="33155alb-52ef-4890-8fa0-3c2bf310059b" ac:name="confiform-field-definition" ac:schema-version="1">

```

```

<ac:parameter ac:name="fieldName">t</ac:parameter>
<ac:parameter ac:name="fieldLabel">t</ac:parameter>
<ac:parameter ac:name="type">text</ac:parameter>
</ac:structured-macro>
</p>
<p>
    <ac:structured-macro ac:macro-id="b4ec16d4-1863-4bed-8e3a-288e64ca86b3" ac:name="confiform-field-definition-rules" ac:schema-version="1">
        <ac:parameter ac:name="values">initCfDialogPages();</ac:parameter>
        <ac:parameter ac:name="action">Run custom JavaScript</ac:parameter>
    </ac:structured-macro>
</p>
</ac:rich-text-body>
</ac:structured-macro>
<ac:structured-macro ac:macro-id="3949caa7-d618-40dd-aea2-6abbc74dd0ef" ac:name="confiform-entry-register" ac:schema-version="1">
    <ac:parameter ac:name="formName">myform</ac:parameter>
    <ac:parameter ac:name="embedded">true</ac:parameter>
    <ac:parameter ac:name="atlassian-macro-output-type">INLINE</ac:parameter>
    <ac:rich-text-body>
        <ac:structured-macro ac:macro-id="fd6f85d6-3796-4d32-9beb-d4b400e9f861" ac:name="html-div" ac:schema-version="1">
            <ac:parameter ac:name="Id">mypage1</ac:parameter>
            <ac:parameter ac:name="atlassian-macro-output-type">INLINE</ac:parameter>
            <ac:rich-text-body>
                <p>This is my page 1</p>
            <ac:structured-macro ac:macro-id="1e5dc3bd-2356-4ccc-9f56-b242bc7e4344" ac:name="info" ac:schema-version="1">
                <ac:rich-text-body>
                    <p>Hello info</p>
                </ac:rich-text-body>
            </ac:structured-macro>
            <p>
                <br/>
            </p>
            <p>
                <br/>
            </p>
            <ac:structured-macro ac:macro-id="8973e4dd-dc98-401b-8efe-b9378eab10cc" ac:name="confiform-field" ac:schema-version="1">
                <ac:parameter ac:name="fieldName">t</ac:parameter>
                <ac:parameter ac:name="withLabel">true</ac:parameter>
            </ac:structured-macro>
            <p>
                <br/>
            </p>
            <p>
                <br/>
            </p>
            <ac:rich-text-body>
        </ac:structured-macro>
        <ac:structured-macro ac:macro-id="05ba0f6e-f6ec-4c39-8cd2-1ede45abf8d0" ac:name="html-div" ac:schema-version="1">
            <ac:parameter ac:name="Css">display:none;</ac:parameter>
            <ac:parameter ac:name="Id">mypage2</ac:parameter>
            <ac:parameter ac:name="atlassian-macro-output-type">INLINE</ac:parameter>
            <ac:rich-text-body>
                <p>This is my page 2</p>
            <ac:structured-macro ac:macro-id="864d3e15-a6c1-48b0-9fb8-be7641bf356a" ac:name="warning" ac:schema-version="1">
                <ac:rich-text-body>
                    <p>Hello warning</p>
                </ac:rich-text-body>
            </ac:structured-macro>
            <ac:rich-text-body>
        </ac:structured-macro>
        <ac:structured-macro ac:macro-id="8c91d379-5a55-4bd3-8d50-25e5cf7d920d" ac:name="html-div" ac:schema-version="1">
            <ac:parameter ac:name="Css">display:none;</ac:parameter>
            <ac:parameter ac:name="Id">mypage3</ac:parameter>
            <ac:parameter ac:name="atlassian-macro-output-type">INLINE</ac:parameter>
            <ac:rich-text-body>
                <p>This is my page 3</p>
            <p>
                <ac:structured-macro ac:macro-id="60359d4d-5e53-491b-947f-797f313f7808" ac:name="status" ac:schema-

```

```
version="1">
    <ac:parameter ac:name="colour">Green</ac:parameter>
    <ac:parameter ac:name="title">I am fine - this is the last page</ac:parameter>
</ac:structured-macro>
</p>
<p>
    <br/>
</p>
</ac:rich-text-body>
</ac:structured-macro>
<p>
    <ac:structured-macro ac:macro-id="f00908e9-4265-4f43-ba12-d01131f7f522" ac:name="multi-page-div" ac:schema-version="1">
        <ac:parameter ac:name="Pages">mypage1,mypage2,mypage3</ac:parameter>
        <ac:parameter ac:name="noAutoInit">false</ac:parameter>
        <ac:parameter ac:name="manualInit">true</ac:parameter>
    </ac:structured-macro>
</p>
</ac:rich-text-body>
</ac:structured-macro>
<p>
    <br/>
</p>
<p>
    <br/>
</p>
<p>
    <br/>
</p>
<p>
    <br/>
</p>
```