

Create Jira issue with webservice connection and save only jira key

Yes, you can create Jira issue with WebService IFTTT action (usual IFTTT to create Jira issues **will not work for anonymous users** as it uses Atlassian Application link to connect to your Jira and that will not be available for anonymous users, while web service connection is available to anyone, unless you tell otherwise (setting up connection restrictions))

Here is the demo (creates the issue and stores the Jira key back)

Storage format

```
<ac:structured-macro ac:macro-id="634f4a34-b8ba-464d-b222-e123d65cc4e0" ac:name="conform" ac:schema-version="1">
  <ac:parameter ac:name="formName">jitest</ac:parameter>
  <ac:parameter ac:name="showOnlyOwnRecords">true</ac:parameter>
  <ac:parameter ac:name="registrationFormTitle">Create Jira issue with ConfiForms Webservice connection</ac:parameter>
  <ac:rich-text-body>
    <ac:structured-macro ac:macro-id="dd25632e-211e-4820-8754-836d4ade9236" ac:name="conform-entry-register" ac:schema-version="1">
      <ac:parameter ac:name="overrideSaveButtonLabel">Create</ac:parameter>
      <ac:parameter ac:name="registrationButtonLabel">Register me</ac:parameter>
      <ac:parameter ac:name="embedded">true</ac:parameter>
      <ac:parameter ac:name="atlassian-macro-output-type">INLINE</ac:parameter>
      <ac:rich-text-body>
        <p>
          <br/>
        </p>
      </ac:rich-text-body>
    </ac:structured-macro>
  </p>
  <ac:structured-macro ac:macro-id="8a572845-1d28-4560-a4d8-f8102317e419" ac:name="conform-field-definition" ac:schema-version="1">
    <ac:parameter ac:name="fieldName">summary</ac:parameter>
    <ac:parameter ac:name="fieldLabel">Summary</ac:parameter>
    <ac:parameter ac:name="type">text</ac:parameter>
  </ac:structured-macro>
</p>
<p>
  <ac:structured-macro ac:macro-id="2e5a8660-272b-43f6-801d-a3131c3665c5" ac:name="conform-field-definition" ac:schema-version="1">
    <ac:parameter ac:name="fieldName">desc1</ac:parameter>
    <ac:parameter ac:name="fieldLabel">Description</ac:parameter>
    <ac:parameter ac:name="type">text</ac:parameter>
  </ac:structured-macro>
</p>
<p>
  <ac:structured-macro ac:macro-id="7d641f3b-1fd7-4e47-a63e-a2b040782730" ac:name="conform-field-definition" ac:schema-version="1">
    <ac:parameter ac:name="fieldName">desc2</ac:parameter>
    <ac:parameter ac:name="fieldLabel">More details:</ac:parameter>
    <ac:parameter ac:name="type">textarea</ac:parameter>
  </ac:structured-macro>
</p>
<p>
  <ac:structured-macro ac:macro-id="7c8f347e-7704-441f-92f2-990cac31a7d5" ac:name="conform-field-definition" ac:schema-version="1">
    <ac:parameter ac:name="css">width:100px;</ac:parameter>
    <ac:parameter ac:name="fieldName">jk</ac:parameter>
    <ac:parameter ac:name="fieldLabel">Jira key</ac:parameter>
    <ac:parameter ac:name="type">read_only</ac:parameter>
  </ac:structured-macro>
</p>
<p>
```

```

        <ac:structured-macro ac:macro-id="a06f0ccf-0e36-4d07-b47d-cb38a345c0fe" ac:name="confiorm-field-
definition-rules" ac:schema-version="1">
        <ac:parameter ac:name="condition">id:[empty]</ac:parameter>
        <ac:parameter ac:name="fieldName">jk</ac:parameter>
        <ac:parameter ac:name="action">Hide field</ac:parameter>
        </ac:structured-macro>
    </p>
    <ac:structured-macro ac:macro-id="0cc4d8ec-9be2-4e16-b398-9427586d81a9" ac:name="confiorm-ifttt" ac:schema-
version="1">
        <ac:parameter ac:name="action">WebService Request</ac:parameter>
        <ac:parameter ac:name="extras">4bb4c41a51f289a07507d50a1b841a4d</ac:parameter>
        <ac:parameter ac:name="event">onCreated</ac:parameter>
        <ac:parameter ac:name="title">/rest/api/2/issue/</ac:parameter>
        <ac:parameter ac:name="extras2">X-Atlassian-Token: no-check;Content-Type: application/json;Content-Type:
charset=UTF-8</ac:parameter>
        <ac:parameter ac:name="resultName">myjira</ac:parameter>
        <ac:parameter ac:name="who">POST</ac:parameter>
        <ac:rich-text-body>
            <ac:structured-macro ac:macro-id="46d25e82-d4db-4e38-9b96-f5c6159c473f" ac:name="noformat" ac:schema-
version="1">
                <ac:plain-text-body><![CDATA[{
                    "fields": {
                        "project":
                        {
                            "key": "JTEST"
                        },
                        "summary": "[entry.summary.escapeJSON]",
                        "assignee":{"name":"admin"},
                        "description": "[entry.desc1.escapeJSON] \n [entry.desc2.escapeJSON]",
                        "issuetype": {
                            "name": "Bug"
                        }
                    }
                }]]></ac:plain-text-body>
            </ac:structured-macro>
        </ac:rich-text-body>
    </ac:structured-macro>
    <p>
        <br/>
    </p>
    <p>
        <br/>
    </p>
    <ac:structured-macro ac:macro-id="a9eeb29b-9cf1-4e02-bd92-e9065673a95d" ac:name="confiorm-ifttt" ac:schema-
version="1">
        <ac:parameter ac:name="extras4">true</ac:parameter>
        <ac:parameter ac:name="action">Create ConfiForms Entry</ac:parameter>
        <ac:parameter ac:name="event">onCreated</ac:parameter>
        <ac:parameter ac:name="title">entryId=[entry.id]&jk=${iftttResult_myjira}</ac:parameter>
        <ac:rich-text-body>
            <p>
                <br/>
            </p>
        </ac:rich-text-body>
    </ac:structured-macro>
    <ac:structured-macro ac:macro-id="434fb056-7c11-43cd-a049-8e92847a9e43" ac:name="confiorm-ifttt" ac:schema-
version="1">
        <ac:parameter ac:name="extras4">true</ac:parameter>
        <ac:parameter ac:name="action">Create ConfiForms Entry</ac:parameter>
        <ac:parameter ac:name="event">onCreated</ac:parameter>
        <ac:parameter ac:name="title">entryId=[entry.id]&jk=[entry.jk.asJSON.key]</ac:parameter>
        <ac:rich-text-body>
            <p>
                <br/>
            </p>
        </ac:rich-text-body>
    </ac:structured-macro>
    </ac:rich-text-body>
</ac:structured-macro>
<ac:structured-macro ac:macro-id="d309c641-56ef-46cb-b01f-19590d41605e" ac:name="confiorm-table" ac:schema-
version="1">

```

```
<ac:parameter ac:name="formName">ji</ac:parameter>
<ac:rich-text-body>
  <p>
    <ac:structured-macro ac:macro-id="9a9109ce-a69b-4cea-8e88-a5404d899bc3" ac:name="confiiform-field" ac:
schema-version="1">
      <ac:parameter ac:name="fieldName">jk</ac:parameter>
    </ac:structured-macro>
  </p>
  <p>
    <ac:structured-macro ac:macro-id="18b7e9fe-30c3-4a04-886e-6a47446af441" ac:name="confiiform-field" ac:
schema-version="1">
      <ac:parameter ac:name="fieldName">created</ac:parameter>
    </ac:structured-macro>
  </p>
</ac:rich-text-body>
</ac:structured-macro>
```